



EC -TY PE EX AMINATION C ERTIFIC ATE (MODULE B)

Certificate no.:
MEDB00004A0
Revision no.:
1

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV AS under the authority of the Government of Norway.

This is to certify:

that the **Surface materials and floor coverings with low flame-spread characteristics: - decorative veneers**

with type designation(s)
Chemetal decorative veneers

issued to

Chemetal, Inc.
Easthampton, USA

is found to comply with the Implementing Regulation (EU) 2025/1533 for
Item no. **MED/3.18a** (Row 1 of 1) according to the following
requirements:


SOLAS 74 Reg. II-2/3, IMO Res. MSC.36(63)-(1994 HSC Code) 7, IMO Res. MSC.97(73)-(2000 HSC Code) 7, IMO MSC/Circ.1120, SOLAS 74 Reg. II-2/5, SOLAS 74 Reg. II-2/6, SOLAS 74 Reg. X/3

Further details of the equipment and conditions for certification are given overleaf.

Date of issue: **2025-10-03**

Expiry date: **2030-10-02**

DNV local unit:
Certification & Inspection Services



for **DNV AS**

Approval Engineer:
Kristin Grønnæss Hovden

Notified Body
no.: **0575**

Christine Mydlak-Röder
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the Agreement between the United States of America and the EEA EFTA states on the mutual recognition of Certificates of Conformity for Marine Equipment signed 17 October 2005, and amended by Decision No 1/2023 dated August 21st, 2023.



The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

Certificate no.: **MEDB00004A0**
Revision no.: **1**

Product description

"Chemetal decorative veneers" are available in the following three (3) variants:

1. Homapal High Pressure Metallic Laminates: #200 series, 315, 317, 318, 340, #700 series.

Composed of copper or aluminium foil with a thickness of 0.05 mm attached to a high pressure laminate (HPL) with a thickness of 1.04 mm. The surface is sealed with an 0.005 mm thick transparent layer of UV lacquer type 'RD1383' (manufactured by R&D coatings Inc.).

Total product thickness: 1.09 mm.

Density: 0.002 g/mm³.

2. Pure metal (aluminium, brass, copper) with UV lacquer: #100~103, 303, 304, 306, 310, 314, 325, 335, 337, 338 346, 349, 350, 352, 354, #400 series, #500 series.

Composed of pure aluminium, bright aluminium or bright brass aluminium metal sheet. The surface is sealed with an 0.005 mm thick transparent layer of UV lacquer type 'RD1383' (manufactured by R&D coatings Inc.).

Total product thickness: 0.51 mm - 0.81 mm.

Density: 0.0014 - 0.0027 g/mm³.

3. Pure metal: #800 series, #900 series

Composed of pure aluminium, brass or copper metal sheets.

Application/Limitation

Approved for use as low flame spread surface material, not generating excessive quantities of smoke nor toxic products in fire.

The products may be applied to any metallic and non-combustible base if the product would not need any adhesive or combustible material layer.

If an adhesive is used to bond this product to its base, testing of the total combination of this product applied to its base in accordance with IMO FTP Code part 5 and 2 is required.

If a combustible layer is applied to the product, the total combination of this product with this layer in accordance with IMO FTP Code part 5 and 2 is required.

Approved colours for the variants under 'Product description':

1. Homapal High Pressure Metallic Laminates: #200 series, 315, 317, 318, 340

Approved colour (tested colour #317 – Aurora): Brown

Max. organic content: 98%

2. Pure metal (aluminium, brass, copper) with UV lacquer: #100~103, 303, 304, 306, 310, 314, 325, 335, 337, 338 346, 349, 350, 352, 354, #400 series, #500 series, #700 series.

Approved colour (tested colour #414 – Nomadic and #702 – Brushed Aluminium): Silver/Brown

Max. organic content: 98%

3. Pure metal: #800 series, #900 series :

Approved colour: The metal colours of aluminium, brass or copper.

Maximum gross calorific value shall be documented separately where applicable, ref. SOLAS Chapter II-2 Reg. 5.3.2.



Each product or series are to be supplied with its manual for installation/application and maintenance.

Type Examination documentation

Form code: MED 2101.NOR

Revision: 2025-03

www.dnv.com

Page 2 of 3

Certificate no.: **MEDB00004A0** Revision
no.: **1**

Tests carried out

Tested according to IMO 2010 FTP Code part 5 and 2.

Marking of product

The product or packing is to be marked with name and address of manufacturer, type designation, fire technical rating, the Mark of Conformity and USCG approval number, if applicable (see page 1).

